



SPECIFICATION SHEET

16-340LG



G-TEK® POLYKOR™ BLENDED GLOVE WITH DOUBLE-DIPPED NITRILE COATED MICRO-SURFACE GRIP

- Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Double-dipped nitrile micro-surface coating helps extend the life of the glove and provide excellent abrasion resistance
- Knit wrist helps prevent dirt and debris from entering the glove
- Cotton color binding denotes sizing
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- General duty
- Parts assembly
- Sharp small parts handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	PolyKor™ Shell with Nitrile Micro-Surface Coating				
CONSTRUCTION	Seamless Knit				
COLOR	Shell: ■ Hi-Vis Lime Green / Coating: ■ Black				
CUFF STYLE	Continuous knit				
SIZES	S - XXL				
PACKAGING	1 pair per bag, 12 pairs per dozen, 6 dozen per case				
CASE DIMENSIONS	14.2" x 11.8" x 12.6" / 36cm x 30cm x 32cm				
CASE WEIGHT	S	M	L	XL	XXL
	11.8 lb 5.4 kg	12.3 lb 5.6 kg	13.5 lb 6.1 kg	14 lb 6.4 kg	15 lb 6.9 kg
COO	China				

PERFORMANCE PROPERTIES

EN388: 4543	ANSI Cut Level 3					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

BARCODES

ITEM	BAG	DOZEN	CASE
■ 16-340LG/S	---	01616314130709	02616314130708
■ 16-340LG/M	---	01616314130693	02616314130692
■ 16-340LG/L	---	01616314130686	02616314130685
■ 16-340LG/XL	---	01616314130716	02616314130715
■ 16-340LG/XXL	---	01616314130723	02616314130722



DIMENSIONS (in/cm)

	S	M	L	XL	XXL
A	9.3 / 23.7	9.7 / 24.7	10.1 / 25.7	10.5 / 26.6	10.7 / 27.2
B	3.6 / 9.2	3.9 / 9.9	4.1 / 10.4	4.2 / 10.6	4.4 / 11.3
H	■ Red	■ Yellow	■ Brown	■ Black	■ Sky Blue

