

SPECIFICATION SHEET







G-TEK® CR SEAMLESS KNIT POLYKOR™ BLENDED GLOVE WITH ACRYLIC LINING AND DOUBLE-DIPPED LATEX COATED MICRO-SURFACE GRIP

- · Seamless construction offers increased comfort and breathability
- PolyKor™ shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Double-dipped latex "Micro-Surface" coated palm and knuckles help extend the life of the glove and provide excellent abrasion resistance
- Knit wrist helps prevent dirt and debris from entering the glove
- Washable, resistant to chemicals, water, and ultraviolet light

APPLICATIONS

- Electronics
- · Glass cutting
- · Sheet metal handling
- · Parts assembly
- · Sharp small parts handling
- Construction
- · General duty applications

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

MATERIAL	13 gauge PolyKor™ outer shell/acrylic inner shell with latex				
COLOR	Shell: ☐ Salt & Pepper / Coating: ☐ Blue/Black				
CUFF STYLE	Continuous knit				
SIZES	S - XXL				
PACKAGING	12 pair per dozen, 6 dozen per case				
CASE SIZE	31.5" x 11.8" x 10.2" / 80cm x 30cm x 26cm				
CASE WEIGHT	S	M	L	XL	XXL
	20.5 lbs 9.3 kg	21 lbs 9.5 kg	22.3 lbs 10.1 kg	24 lbs 10.9 kg	24.3 lbs 11 kg
C00	China				

PERFORMANCE PROPERTIES

EN388: 2543	ANSI Cut Level 3					
ABRASION	0	1	2	3	4	-
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-

BARCODES

ITFM	BAG	DOZEN	CASE	
IILIVI	DAU	DUZLIN	UAGL	
■ 16-820/S		01616314131096	02616314131095	
■ 16-820/M		01616314131089	02616314131088	
■ 16-820/L		01616314131072	02616314131071	
□ 16-820/XL		01616314131102	02616314131101	
■ 16-820/XXL		01616314131119	02616314131118	



DIMENSIONS (in/cm)

		S	M	L	XL	XXL
I	A	9.8 / 25	10.2 / 26	10.4 / 26.5	10.8 / 27.5	11 / 28
	В	4.1 / 10.3	4.2 / 10.7	4.3 / 11	4.5 / 11.3	4.6 / 11.7
	н	Red	Yellow	Brown	Black	Sky Blue

