



# SPECIFICATION SHEET

## 19-D355



### G-TEK® 3GX, 13 GAUGE DYNEEMA® DIAMOND BLENDED SHELL WITH FOAM NITRILE COATED PALM, FINGERS AND KNUCKLES

- Washable, resistant to chemicals, water and ultraviolet light.
- Seamless construction
- Foam Nitrile coated palm and knuckles are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Dyneema® Diamond blended shell is lightweight and provides excellent dexterity, tactile sensitivity and cut resistance
- Cotton color binding denotes sizing

### APPLICATIONS

- Electronics
- Glass cutting
- Sheet metal handling
- Parts assembly
- Sharp small parts handling
- Construction
- Other general duty applications

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

### TECHNICAL DATA

MATERIAL	Shell: Dyneema® Diamond / Coating: Nitrile			
COLOR	Shell: ■ Salt & Pepper / Coating: ■ Black			
CUFF STYLE	Continuous Knit			
SIZES	S - XL			
PACKAGING	12 pairs per dozen, 6 dozen per case			
CASE	11.8" x 12.6" x 14.2" / 30cm x 32cm x 36cm			
CASE WEIGHT	S	M	L	XL
	9 lbs 4.1 kg	9.5 lbs 4.3 kg	11 lbs 5 kg	12.1 lbs 5.5 kg
COO	China			

### PERFORMANCE PROPERTIES

EN388: 4343	ANSI Cut Level 3					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5

### BARCODES

ITEM	BAG	DOZEN	CASE
■ 19-D355/S	616314167874	01616314167873	02616314167872
■ 19-D355/M	616314167867	01616314167866	02616314167865
■ 19-D355/L	616314167850	01616314167859	02616314167858
■ 19-D355/XL	616314167881	01616314167880	02616314167889



### DIMENSIONS (in/cm)

	S	M	L	XL
<b>A</b>	8.7 / 22	9.1 / 23	9.4 / 24	9.8 / 25
<b>B</b>	3.9 / 10	4.1 / 10.5	4.3 / 11	4.5 / 11.5
<b>H</b>	■ Red	■ Yellow	■ Brown	■ Black

