



# SPECIFICATION SHEET

## 56-425



### MAXIDRY® ULTRA LIGHTWEIGHT NITRILE GLOVE, ¾ DIPPED WITH SEAMLESS KNIT NYLON / LYCRA® LINER AND NON-SLIP GRIP

- Seamless string knit shell is comfortable and flexible
- Foam nitrile coatings are compatible with light oils and will provide a good grip and excellent abrasion resistance
- Increased resistance to oils via ATG's LiquiTech® technology
- Synthetic coating combined with an industry leading super light seamless knit liner
- Locking cuff ensures the glove doesn't slip on the hand.
- The micro-cup non-slip grip finish allows for a controlled and superior grip in oily and wet applications
- All ingredients used in the manufacturing and construction of this product are compliant with the REACH legislation

### APPLICATIONS

- Precision handling in oily and wet environments
- Engine, power train, gear box, transmission, and shock absorber assembly
- Handling small castings, small components, and parts
- General handling and maintenance

### CARE INSTRUCTIONS

Use commercial laundry soap or detergent (do NOT use dry cleaning solutions) Wash in warm to medium hot water, do not exceed 104°F (40° C). Wash for 10 minutes and rinse in cold water. Repeat wash and rinse if soiling is especially heavy. Tumble dry - maximum temperature 140°F (60° C).

### TECHNICAL DATA

|             |  |                 |               |                 |               |
|-------------|--|-----------------|---------------|-----------------|---------------|
| MATERIAL    | Nitrile, nylon, Lycra®                           |                 |               |                 |               |
| COLOR       | ■ Purple / ■ Black                               |                 |               |                 |               |
| CUFF STYLE  | Continuous knit                                  |                 |               |                 |               |
| SIZES       | S - XXL  |                 |               |                 |               |
| PACKAGING   | 12 pairs per dozen, 6 dozen per case             |                 |               |                 |               |
| CASE        | 20.0" x 11.8" x 10.8" / 50.8cm x 30.0cm x 27.4cm |                 |               |                 |               |
| CASE WEIGHT | S  | M               | L             | XL              | XXL           |
|             | 15.4lbs / 7.0kg                                  | 16.5lbs / 7.5kg | 17.6lbs / 8kg | 18.7lbs / 8.5kg | 19.8lbs / 9kg |
| COO         | Sri Lanka  |                 |               |                 |               |

### PERFORMANCE PROPERTIES

|             |   |   |   |   |   |   |
|-------------|---|---|---|---|---|---|
| EN388: 4121 |   |   |   |   |   |   |
| ABRASION    | 0 | 1 | 2 | 3 | 4 | - |
| CUT         | 0 | 1 | 2 | 3 | 4 | 5 |
| TEAR        | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE    | 0 | 1 | 2 | 3 | 4 | - |

### BARCODES

| ITEM         | BAG | DOZEN          | CASE           |
|--------------|-----|----------------|----------------|
| ■ 56-425/S   | --- | 01616314117083 | 02616314117082 |
| ■ 56-425/M   | --- | 01616314117076 | 02616314117075 |
| ■ 56-425/L   | --- | 01616314117069 | 02616314117068 |
| ■ 56-425/XL  | --- | 01616314117090 | 02616314117099 |
| ■ 56-425/XXL | --- | 01616314117106 | 02616314117105 |



### DIMENSIONS (in/cm)

|                  | S          | M          | L          | XL         | XXL        |
|------------------|------------|------------|------------|------------|------------|
| <b>A</b>         | 9.8 / 25.0 | 9.8 / 25.0 | 9.8 / 25.0 | 9.8 / 25.0 | 9.8 / 25.0 |
| <b>B</b>         | 3.2 / 8.2  | 3.3 / 8.4  | 3.7 / 9.4  | 3.8 / 9.7  | 3.9 / 10.0 |
| Thickness: 1.3mm |            |            |            |            |            |

